

borg &
overström

ELITE



Offering added enhancement through refined styling, the borg & overström Elite boasts all the features and options of the Classic, plus other user benefits. These include a larger dispensing area, integral cup dispenser and the option of sparkling water, giving a distinctive edge to your corporate refreshment system.

PRESTIGIOUS POINT-OF-USE COOLER OF STURDY CONSTRUCTION

TOUCH-PANEL CONTROLS AND INTEGRAL CUP DISPENSER

AUTO-LIT DISPENSING AREA OF GENEROUS DIMENSIONS

AVAILABLE AS FLOOR-STANDING OR COUNTER-TOP

A CHOICE OF WATER OPTIONS, INCLUDING HOT, AMBIENT, COLD, DIRECT-CHILL AND SPARKLING

borg & overström

ELITE



MACHINE TYPE (see key)	●	●	○	○	○	○
COOLING SYSTEM						
Thermostatic Control Regulated	●	●	●	●	●	●
Ice Bank Direct Chill	–	–	●	●	●	●
Stainless Steel Tank	●	●	–	–	–	–
HEATING SYSTEM						
Stainless Steel Tank	–	●	–	●	–	–
Tank Size (litres)	–	2	–	2	–	2
Easy change tank	–	●	–	●	–	–
COLOUR						
Silver	●	●	●	●	●	●
Graphite	–	–	–	–	–	–
COUNTER-TOP DIMENSIONS						
Model Number	728	728H	DC728	DC728H	–	–
Width (mm)	325	325	325	325	–	–
Depth (mm)	380	380	380	380	–	–
Height (mm)	475	475	475	475	–	–
FLOOR-STANDING DIMENSIONS						
Model Number	798	798H	DC798	DC798HA	DC798S	DC798HS
Width (mm)	325	325	325	325	325	325
Depth (mm)	365	365	365	365	365	365
Height (mm)	1060	1060	1060	1060	1060	1060
STORAGE BASE DIMENSIONS						
Internal Width (mm)	320	320	320	320	320	320
Internal Depth (mm)	245	245	245	245	245	245
Internal Height (mm)	550	550	550	550	550	550
POWER REQUIREMENTS						
Hertz	50	50	50	50	50	50
Volts	220-240	220-240	220-240	220-240	220-240	220-240
MAX POWER CONSUMPTION						
Cold & Ambient (W)	95	95	95	95	95	95
Cold & Hot (W)	–	545	–	545	–	545
COLD TEMPERATURE						
Min C	4	4	2	2	2	2
Max C	11	11	11	11	11	11
HOT TEMPERATURE						
Max C	–	92	–	92	–	92
DISPENSE LEVEL						
Height (mm)	210	210	210	210	210	210
THROUGHPUT LITRES PER HOUR						
Cold	12	12	22	22	22	22
Hot	–	6	–	6	–	6

KEY Direct Chill ● Cold ● Sparkling ○ Ambient ● Hot ●